

TME Series

Mobile Work Platform

- ✘ A revolutionary design of mast provides the most stable and compact mast in the industry.
- ✘ Provides access to overhead fixture and stocked shelves much safer than traditional ladders or scaffolding.
- ✘ Available in AC or DC power.
- ✘ Suitable for single person to work upraised.
- ✘ Maximum platform height: 6m, 8m, 10m.
- ✘ Power supply: Single phase AC as standard;



TM-E1006



TM-E2006



| Model | | | TM-E1006 | TM-E1008 | TM-E2010 | TM-E2012 |
|----------------------|------|--------|-----------|-----------|-----------|-----------|
| Max. Platform Height | (mm) | | 6000 | 8000 | 10000 | 12000 |
| Working Height | (mm) | | 8000 | 10000 | 12000 | 14000 |
| Min. Platform Height | (mm) | | 580 | 580 | 1850 | 2050 |
| Ground Clearance | (mm) | | 60 | 60 | 80 | 80 |
| Lift Rated Capacity | (kg) | | 150 | 125 | 250 | 200 |
| Platform Size | (mm) | | 630x650 | 630x650 | 1500x600 | 1500x600 |
| Outspread Size | (mm) | | 2050x1850 | 2050x1850 | 2200x1950 | 2300x2600 |
| Electrical | AC | (V) | | | 220-240 | |
| Source | DC | (V) | | | 24 | |
| Aneroid Battery | | (V/Ah) | | | 2x12/75 | |
| Charger | | (V/A) | | | 24/15 | |
| Lifting | AC | (V/Kw) | | | 220/1.5 | |
| Motor | DC | (V/Kw) | 24/2 | 24/2 | 24/2 | 24/2 |
| Overall Length | (mm) | | 1430 | 1430 | 1800 | 1800 |
| Overall Width | (mm) | | 840 | 840 | 850 | 900 |
| Overall Height | (mm) | | 1950 | 2050 | 1800 | 2050 |